

Intelagrid[®] Technology Solutions

intelaMeter[™] Electric

General Electric I-210+ electric meter with NIC



Intelagrid's GE I-210+ single-phase meter with an integrated underclass ZigBee Network Interface Card (NIC). The integrated NIC provides wireless MESH networking capability to communicate with Intelagrid's ecoNet Gateway. The intelaMeter NIC includes an open, standards-based platform that supports two way, real time communication between the utility and its customers. Additionally, the intelaMeter acts as a communication repeater for additional services such as Demand Side Management (DSM) and Smart Home command and control products. The intelaMeter products provide utilities with advanced metering, outage and restoration detection, and demand response. Using Intelagrid's web based intelaHome portal, consumers can access real time information regarding their energy usage and history from a computer, mobile phone, or ecoStat in home display.

The GE I-210+ meter is a highly adopted solid state electricity meter that provides unparalleled digital accuracy, reliability, and cost effectiveness. Engineered for a wide range of needs in the residential market, the I-210+ provides multiple application options to meet current and future requirements. The I-210+ is a solid state single phase electric meter designed for the evolving requirements of the utility industry.

Technical Specifications

Intelagrid Part Number	intelaMeter GE I-210+
Interface	ZigBee Wireless (IEEE 802.15.4 compliant)
Input Power	100 – 400 VAC 50-60 Hz
Signal Rate	240 kbps
Power Consumption	0.8 Watts/ 7.9 VA @ 240VAC
Mechanical Dimensions	5.5" W x 3.75" H x 1.1"D
Weight	.22 Kg
EMC Standard Compliance	EN61000-4-4: 1995
Safety Standard Compliance	EN61000-4-5:1995 Category IV
Temperature	-40 C to +85 C
Humidity	0% - 95%
Accuracy	Exceeds ANSI C12.20 0.5 accuracy class
Complies with Standards	FCC Part 15, ANSI C12.1—2001, ANSI C12.10 –1997, ANSI C37.90.1—1989
Encryption	Standard AES /DES Capable
Frequency	2400 MHz to 2483.5 MHz, 16-MHz channels
RX Sensitivity	-95 dBm nominal
TX Power	-32 dbm to +20 dbm (100mW)

© 2009 Intelagrid LLC. All rights reserved. The Intelagrid name and logo and all related product and service names, design marks and slogans are trademarks, service marks or registered trademarks of Intelagrid LLC. All other product and service marks are the property of their respective owners.

KEY FEATURES

- Standards based communication IEE 802.15.4 ZigBee protocol
- Non-volatile memory storage
- Secure DES support
- Instant on-demand reading
- Over-the-air (OTA) enabled firmware update support
- Voltage measuring
- Demand Information
- Acquires time stamped interval metering data
- Full Two-way communication